MOTIP DUPLI GROUP

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.04.2013 Version number 3 Revision: 13.03.2013

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Distein Forstmarkierfarbe Neonfarbtöne
- · Article number:

132445, 132476, 132483, 132490, 132520, 132544, 132551, 132552, 201318, 201325, 201332, 201349, 201356, 201363, 201370, 201387, 202322, 202339, 202346, 202353, 202360, 202377, 202384, 202391, 209215, 209222, 209239, 209246, 209253, 209260, 217135, 217142, 217159, 217166, 217173, 217180, 217197, 217203, 217272, 217289, 217296, 217302, 217319, 217326, 217333, 217340, 357671, 647949, 647963, 647970, 647987, 647994, 648014, 648519, 649533

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against --
- · Application of the substance / the preparation Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI GmbH

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49/6266/75-0

sicherheitsdatenblatt@dupli-color.de

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12: Extremely flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



F+ Extremely flammable

· Risk phrases:

12 Extremely flammable.

- · Safety phrases:
 - 2 Keep out of the reach of children.

(Contd. on page 2)

Printing date 04.04.2013 Version number 3 Revision: 13.03.2013

Trade name: Distein Forstmarkierfarbe Neonfarbtöne

(Contd. of page 1)

- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe spray.
- 24/25 Avoid contact with skin and eyes.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (e.g. in the car). Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

- · Classification in accordance with Directive 75/324/EEC: Extremely flammable
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 64742-89-8	Solvent naphtha (petroleum), light aliph.	20-<25%
EINECS: 265-192-2	★ Xn R65	
	♦ Asp. Tox. 1, H304	
CAS: 74-98-6	propane	12.5-<20%
EINECS: 200-827-9	F+R12	
Reg.nr.: 01-2119486944-21	Flam. Gas 1, H220; Press. Gas, H280	1
CAS: 106-97-8	butane	12.5-<20%
EINECS: 203-448-7	F+ R12	
Reg.nr.: 01-2119474691-32	🕟 Flam. Gas 1, H220; Press. Gas, H280	1
CAS: 141-78-6	ethyl acetate	10-<12.5%
EINECS: 205-500-4	★ Xi R36; ♦ F R11	
Reg.nr.: 01-2119475103-46	R66-67	
	♠ Flam. Liq. 2, H225; ♠ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 75-28-5	isobutane	5-<10%
EINECS: 200-857-2	F+ R12	
	🏇 Flam. Gas 1, H220; Press. Gas, H280	1
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	2.5-<5.0%
EINECS: 265-151-9	🗶 Xn R65; 🗶 Xi R38; 🔥 F R11; 👺 N R51/53	
	R67	
	🏇 Flam. Liq. 1, H224; 🗞 Asp. Tox. 1, H304; 🔖 Aquatic]
	Chronic 2, Ĥ411; 🕦 Skin Irrît. 2, H315; STOT ŠE 3, H336	

· Additional information:

The content of Bencene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

Printing date 04.04.2013 Version number 3 Revision: 13.03.2013

Trade name: Distein Forstmarkierfarbe Neonfarbtöne

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

· 6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- $\cdot \, 7.2 \ Conditions \ for \ safe \ storage, \ including \ any \ incompatibilities$
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2B
- · 7.3 Specific end use(s) No further relevant information available.

GB

Printing date 04.04.2013 Version number 3 Revision: 13.03.2013

Trade name: Distein Forstmarkierfarbe Neonfarbtöne

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL () Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

141-78-6 ethyl acetate

WEL () Short-term value: 400 ppm Long-term value: 200 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. • Respiratory protection: Not required.

· Protection of hands:



Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Butyl rubber, BR
- · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min

Xylene: 42 min

· Eye protection: Safety glasses

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

(Contd. on page 5)

Printing date 04.04.2013 Version number 3 Revision: 13.03.2013

Trade name: Distein Forstmarkierfarbe Neonfarbtöne

	(Contd. of page
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	8300 hPa
· Density at 20 °C:	0.78 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	ter): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC-(EU)	
	619.4 g/l
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

LD/LC30 values relevant for classification:

141-78-6 ethyl acetate

 Oral
 LD50
 5620 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 1600 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 6)

Printing date 04.04.2013 Version number 3 Revision: 13.03.2013

Trade name: Distein Forstmarkierfarbe Neonfarbtöne

· Additional toxicological information: Vapours have narcotic effect.

(Contd. of page 5)

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging
	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including
	empty pressure containers

- · Uncleaned packaging:
- Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

14 Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 2 5F Gases.

(Contd. on page 7)

Printing date 04.04.2013 Version number 3 Revision: 13.03.2013

Trade name: Distein Forstmarkierfarbe Neonfarbtöne

	(Contd. o	f page
· Label	2.1	
· IMDG, IATA		
· Class	2.1	
· Label	2.1	
· 14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
EMS Number:	F- D , S - U	
14.7 Transport in bulk according to Anne	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	1L	
Transport category	2	
Tunnel restriction code	D	

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmfull: may cause lung damage if swallowed
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

(Contd. on page 8)

Printing date 04.04.2013 Version number 3 Revision: 13.03.2013

Trade name: Distein Forstmarkierfarbe Neonfarbtöne

(Contd. of page 7)

· Contact: Anwendungstechnik

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Reglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

GB